

**§ 250.1001 Definitions.**

Terms used in this subpart shall have the meanings given below:

*DOI pipelines* include:

(1) Producer-operated pipelines extending upstream (generally seaward) from each point on the OCS at which operating responsibility transfers from a producing operator to a transporting operator;

(2) Producer-operated pipelines extending upstream (generally seaward) of the last valve (including associated safety equipment) on the last production facility on the OCS that do not connect to a transporter-operated pipeline on the OCS before crossing into State waters;

(3) Producer-operated pipelines connecting production facilities on the OCS;

(4) Transporter-operated pipelines that DOI and DOT have agreed are to be regulated as DOI pipelines; and

(5) All OCS pipelines not subject to regulation under 49 CFR parts 192 and 195.

*DOT pipelines* include:

(1) Transporter-operated pipelines currently operated under DOT requirements governing design, construction, maintenance, and operation;

(2) Producer-operated pipelines that DOI and DOT have agreed are to be regulated under DOT requirements governing design, construction, maintenance, and operation; and

(3) Producer-operated pipelines downstream (generally shoreward) of the last valve (including associated safety equipment) on the last production facility on the OCS that do not connect to a transporter-operated pipeline on the OCS before crossing into State waters and that are regulated under 49 CFR parts 192 and 195.

*Lease term pipelines* are those pipelines owned and operated by a lessee or operator and are wholly contained within the boundaries of a single lease, unitized leases, or contiguous (not cornering) leases of that lessee or operator.

*Out-of-service pipelines* are those pipelines that have not been used to transport oil, natural gas, sulfur, or produced water for more than 30 consecutive days.

*Pipelines* are the piping, risers, and appurtenances installed for the purpose of transporting oil, gas, sulphur, and produced water. (Piping confined to a production platform or structure is covered in Subpart H, Production Safety Systems, and is excluded from this subpart.)

*Production facilities* means OCS facilities that receive hydrocarbon production either directly from wells or from other facilities that produce hydrocarbons from wells. They may include processing equipment for treating the production or separating it into its various liquid and gaseous components before transporting it to shore.

*Right-of-way pipelines* are those pipelines which—

(1) Are contained within the boundaries of a single lease or group of unitized leases but are not owned and operated by the lessee or operator of that lease or unit,

(2) Are contained within the boundaries of contiguous (not cornering) leases which do not have a common lessee or operator,

(3) Are contained within the boundaries of contiguous (not cornering) leases which have a common lessee or operator but are not owned and operated by that common lessee or operator, or

(4) Cross any portion of an unleased block(s).

**§ 250.1002 Design requirements for DOI pipelines.**

(a) The internal design pressure for steel pipe shall be determined in accordance with the following formula:

$$P = \frac{2(S)(t)}{D} \times (F)(E)(T)$$

For limitations see section 841.121 of American National Standards Institute (ANSI) B31.8 (as incorporated by reference in § 250.198) where—

P = Internal design pressure in pounds per square inch (psi).

S = Specified minimum yield strength, in psi, stipulated in the specification under which the pipe was purchased from the manufacturer or determined in accordance with section 811.253(h) of ANSI B31.8.

D = Nominal outside diameter of pipe, in inches.

### § 250.1003

### 30 CFR Ch. II (7–1–14 Edition)

t = Nominal wall thickness, in inches.

F = Construction design factor of 0.72 for the submerged component and 0.60 for the riser component.

E = Longitudinal joint factor obtained from Table 841.1B of ANSI B31.8 (see also section 811.253(d)).

T = Temperature derating factor obtained from Table 841.1C of ANSI B31.8.

(b)(1) Pipeline valves shall meet the minimum design requirements of American Petroleum Institute (API) Spec 6A (as incorporated by reference in §250.198), API Spec 6D (as incorporated by reference in §250.198), or the equivalent. A valve may not be used under operating conditions that exceed the applicable pressure-temperature ratings contained in those standards.

(2) Pipeline flanges and flange accessories shall meet the minimum design requirements of ANSI B16.5, API Spec 6A, or the equivalent (as incorporated by reference in 30 CFR 250.198). Each flange assembly must be able to withstand the maximum pressure at which the pipeline is to be operated and to maintain its physical and chemical properties at any temperature to which it is anticipated that it might be subjected in service.

(3) Pipeline fittings shall have pressure-temperature ratings based on stresses for pipe of the same or equivalent material. The actual bursting strength of the fitting shall at least be equal to the computed bursting strength of the pipe.

(4) If you are installing pipelines constructed of unbonded flexible pipe, you must design them according to the standards and procedures of API Spec 17J, as incorporated by reference in 30 CFR 250.198.

(5) You must design pipeline risers for tension leg platforms and other floating platforms according to the design standards of API RP 2RD, Design of Risers for Floating Production Systems (FPSs) and Tension Leg Platforms (TLPs) (as incorporated by reference in §250.198).

(c) The maximum allowable operating pressure (MAOP) shall not exceed the least of the following:

(1) Internal design pressure of the pipeline, valves, flanges, and fittings;

(2) Eighty percent of the hydrostatic pressure test (HPT) pressure of the pipeline; or

(3) If applicable, the MAOP of the receiving pipeline when the proposed pipeline and the receiving pipeline are connected at a subsea tie-in.

(d) If the maximum source pressure (MSP) exceeds the pipeline's MAOP, you must install and maintain redundant safety devices meeting the requirements of section A9 of API RP 14C (as incorporated by reference in §250.198). Pressure safety valves (PSV) may be used only after a determination by the Regional Supervisor that the pressure will be relieved in a safe and pollution-free manner. The setting level at which the primary and redundant safety equipment actuates shall not exceed the pipeline's MAOP.

(e) Pipelines shall be provided with an external protective coating capable of minimizing underfilm corrosion and a cathodic protection system designed to mitigate corrosion for at least 20 years.

(f) Pipelines shall be designed and maintained to mitigate any reasonably anticipated detrimental effects of water currents, storm or ice scouring, soft bottoms, mud slides, earthquakes, subfreezing temperatures, and other environmental factors.

### § 250.1003 Installation, testing, and repair requirements for DOI pipelines.

(a)(1) Pipelines greater than 8% inches in diameter and installed in water depths of less than 200 feet shall be buried to a depth of at least 3 feet unless they are located in pipeline congested areas or seismically active areas as determined by the Regional Supervisor. Nevertheless, the Regional Supervisor may require burial of any pipeline if the Regional Supervisor determines that such burial will reduce the likelihood of environmental degradation or that the pipeline may constitute a hazard to trawling operations or other uses. A trawl test or diver survey may be required to determine whether or not pipeline burial is necessary or to determine whether a pipeline has been properly buried.

(2) Pipeline valves, taps, tie-ins, capped lines, and repaired sections that could be obstructive shall be provided with at least 3 feet of cover unless the Regional Supervisor determines that